

BioFlo UTF

BIODEGRADABLE UNIVERSAL TRACTOR FLUID

DESCRIPTION:

BioFlo UTF is formulated from readily biodegradable, high lubricity base oils coupled with proprietary anti-wear and anti-corrosion additives to meet the requirements for Universal Tractor/Transmission Oil (UTTO), drive train/hydraulic fluid. This high performance formula can reduce operating temperatures and component wear in mobile and industrial hydraulic systems. Excellent thermal and oxidative stability assures superior service life with minimal viscosity change over a broad range of operating conditions. **BioFlo UTF** is suitable for use in ecologically sensitive applications or wherever a readily biodegradable, high performance Universal Tractor/Transmission Oil is required.

FEATURES:

- ◆ Superior anti wear protection.
- ◆ Advanced rust and corrosion protection.
- ◆ High viscosity index/temperature stability.
- ◆ Low sustainable operating temperature.

TECHNICAL DATA:

BioFlo		UTF				
ISO Grade:		46				
Specific Gravity:		.913				
Viscosity	ASTM D445					
@ 40°C, cSt:		46				
@ 100°C, cSt:		9.1				
Viscosity Index:	ASTM D2270	197				
Pour Point °F (°C):	ASTM D97	-31 (-35)				
Flash Point °F (°C):	ASTM D92	>470 (243)				
Copper Corrosion:	ASTM D4048	1A				
Rust Test, A & B:	ASTM D665	Pass				
Biodegradability, %:	CEC-L-33-A-94	>60				
Suggested Operating Range		-10F to 180F				

AVAILABLE PACKAGING:

5 Gallon Pails, 55 Gallon Steel or Plastic Drums, 275 Gallon Totes, and Bulk.



BIOBLEND™ RENEWABLE RESOURCES LLC
2439 REEVES ROAD - JOLIET, IL 60436
PHONE: 630.227.1800
www.bioblend.com