

BioGear CO²²⁰

BIODEGRADABLE GEAR & CYCLE OIL

DESCRIPTION:

BioGear CO²²⁰ is a readily biodegradable, non-toxic extreme pressure gear lubricant designed for a variety of industrial and mobile equipment applications. **BioGear CO²²⁰** is designed for multiple applications, such as oil lubricated roller bearings and helical or double helical gear sets. As a general lubricant it can be used on chains, guide rails, levers or any moving parts.

FEATURES:

- ◆ Readily biodegradable, non-toxic.
- ◆ Superior oxidation stability.
- ◆ High Viscosity Index.
- ◆ Advanced rust and corrosion protection.
- ◆ Reduced friction and heat.

TECHNICAL DATA:

BioGear		CO ²²⁰	
ISO Grade:		220	
Recommended for AGMA No:		5EP	
Viscosity	ASTM D445		
@ 40°C, cSt: typical		220	
Viscosity Index:	ASTM D2270	196	
Pour Point, °F (°C):	ASTM D97	0 (-18)	
Flash Point, °F (°C):	ASTM D92	>500 (260)	
FZG Load Stage:	DIN 51354	12	
Timken OK Load		>25lbs	
Copper Corrosion:	ASTM D4048	1A	
Rust Test, A & B	ASTM D1743	Pass	
Biodegradability, %	CEC-L-33-A-94	>95	
Suggested Operating Range		-20F to 150F	

AVAILABLE PACKAGING:

5 Gallon Pails, 55 Gallon Steel or Plastic Drums, 275 Gallon Totes.



BIOBLEND™ RENEWABLE RESOURCES LLC
 2439 REEVES ROAD - JOLIET, IL 60436
 PHONE: 630.227.1800
 www.bioblend.com