

BioLube C&C⁴⁶

BIODEGRADABLE CHAIN & CABLE LUBRICANT

DESCRIPTION:

BioLube C&C⁴⁶ is a readily biodegradable chain and cable lubricant designed for oven and conveyor chains, wire ropes, and cables. Its excellent lubricity and temperature stability provide smooth mechanical performance and superior anti-wear protection. Use **BioLube C&C^{32P}** where a lighter viscosity product is required and more penetration is needed.

FEATURES:

- ◆ Readily biodegradable, nontoxic.
- ◆ Superior temperature & oxidation stability.
- ◆ High Viscosity Index.
- ◆ Excellent EP & anti-wear lubrication.
- ◆ Advanced rust and corrosion protection.

TECHNICAL DATA:

BioLube		C&C ⁴⁶				
ISO Grade:		46				
Specific Gravity:		.913				
Viscosity	ASTM D445					
@ 40°C, cSt:		46				
Viscosity Index:	ASTM D2270	>200				
Pour Point °F (°C):	ASTM D97	0 (-18)				
Flash Point °F (°C):	ASTM D92	>500 (260)				
Copper Corrosion:	ASTM D4048	1A				
Rust Test, A & B:	ASTM D665	Pass				
Biodegradability, %:	CEC-L-33-A-94	>95				
Suggested Operating Range		20 to 170F				

AVAILABLE PACKAGING:

16 oz. Spray Bottles, 5 Gallon Pails, 55 Gallon Steel or Plastic Drums, 275 Gallon Totes, and Bulk.



BIOBLEND™ RENEWABLE RESOURCES LLC
 2439 REEVES ROAD - JOLIET, IL 60436
 PHONE: 630.227.1800
 www.bioblend.com