

BioMotive^{2c}

BIODEGRADABLE 2-CYCLE ENGINE OIL

DESCRIPTION:

BioMotive^{2c} rated *Readily Biodegradable*, environmentally friendly, ash-less and fully synthetic two-cycle engine oil. Applications include direct oil injection or premix, high-performance, water-cooled, and most air-cooled two-cycle engines. **BioMotive^{2c}** contains a unique blend of anti-wear additives and lubricity agents and meets or exceeds the following specifications: JASO FB, API Service TC, TC-W3, TC-WII, TC-W, and the new Honda AF-27 lubricity test. NMMA # is RL 93014J - 2007.

FEATURES:

- ◆ Meets or exceeds relevant two-cycle engine performance tests.
- ◆ Readily miscible in gasoline.
- ◆ Clean lubrication for marine engines, off-road vehicles, and handheld equipment.
- ◆ Enhanced lubricity.
- ◆ Keeps engine parts clean.
- ◆ Minimizes piston ring sticking.
- ◆ Superior rust and corrosion protection.

TECHNICAL DATA:

	BioMotive	2c				
Viscosity	ASTM D445					
@ 40°C, cSt :		44				
@ 100°C, cSt :		8				
Flash Point COC, °C (F):	ASTM D92	140 (284)				
Pour Point, C (F):	ASTM D97	-42 (-44)				
Viscosity Index:	ASTM D2272	149				
Sulfated Ash, wt%	ASTM D874	Nil				
Color	Visual	Purple				
Biodegradability, %:	OECD 301F	66.9				

AVAILABLE PACKAGING:

1 Quart Bottles, 5 Gallon Pails, 55 Gallon Steel or Plastic Drums.



BIOBLEND™ RENEWABLE RESOURCES LLC
 2439 REEVES ROAD - JOLIET, IL 60436
 PHONE: 630.227.1800
 www.bioblend.com