

SynLube VP^{FG}

FOOD GRADE SYNTHETIC VACUUM PUMP LUBRICANT

DESCRIPTION:

Foodstream™ SynLube VP^{FG} Food Grade Synthetic Vacuum Pump Lubricant is formulated from pure synthetic base oils for outstanding oxidative and thermal stability. It is NSF registered as meeting the guidelines of an H1 product for incidental food contact.

SynLube VP^{FG} is fortified with rust and oxidation inhibitors plus antiwear additives to protect against rust, corrosion, oxidation, and wear. This light viscosity oil provides extended life lubrication for tough food processing hydraulic and vacuum pump applications.

FEATURES:

- ◆ NSF H1 Food Grade.
- ◆ Inhibits rust, corrosion and oxidation.
- ◆ Excellent thermal stability and low temperature performance.
- ◆ Will not degrade yellow metals such as brass, bronze or copper.
- ◆ Compatible with all common seal materials.
- ◆ Long life reduces maintenance and disposal costs.

TECHNICAL DATA:

SynLube		VP					
ISO Grade:			15				
Specific Gravity:			.816				
Viscosity							
@40°C, cSt:	ASTM D445		15				
@100°C, cSt:	ASTM D2161		3.58				
Viscosity Index:	ASTM D2270		122				
Pour Point, °F (°C):	ASTM D97		-85 (-65)				
Flash Point, °F (°C):	ASTM D92		370 (188)				
Copper Corrosion:	ASTM D4048		1A				
Rust Test Rating, A & B:	ASTM D665		Pass				

AVAILABLE PACKAGING:

5 Gallon Pails, 55 Gallon Drums, 275 Gallon Totes.



BIOBLEND™ RENEWABLE RESOURCES LLC
 2439 REEVES ROAD - JOLIET, IL 60436
 PHONE: 630.227.1800
 www.bioblend.com