

# TruFlo FG

## FOOD GRADE ANTIWEAR HYDRAULIC FLUIDS

### DESCRIPTION:

*Foodstream*<sup>™</sup> **TruFlo FG** is a general-purpose food grade hydraulic fluid formulated from quality white oils. It includes anti-wear and anticorrosion additives to protect hydraulically operated food processing and packaging equipment. All **TruFlo FG** fluids are NSF registered as meeting the guidelines of an H1 product for incidental food contact.

### FEATURES:

- ◆ Antiwear performance.
- ◆ Inhibits rust and corrosion.
- ◆ Includes defoaming agent.
- ◆ NSF H1 Food Grade.

### TECHNICAL DATA:

TruFlo		FG <sup>32</sup>	FG <sup>46</sup>	FG <sup>68</sup>	FG <sup>100</sup>	FG <sup>150</sup>
ISO Grade:	ASTM D217	32	46	68	100	150
Specific Gravity:	ASTM D1298	.850	.850	.850	.850	.850
Viscosity:						
@ 40°C, cSt:	ASTM D445	32	46	68	100	150
@ 100°C, cSt:	ASTM D2161	5	7	13	16	19
Viscosity Index:	ASTM D2270	>100	>101	>102	>105	>108
Pour Point, °F (°C):	ASTM D97	-5(-15)	-5(-15)	-5(-15)	10(-12)	10(-12)
Flash Point, °F (°C):	ASTM D92	410 (210)	410 (210)	440 (227)	505 (262)	505 (262)
Copper Corrosion:	ASTM D4048	1A	1A	1A	1A	1A
Rust Test, A & B:	ASTM D665	Pass	Pass	Pass	Pass	Pass

### AVAILABLE PACKAGING:

5 Gallon Pails, 55 Gallon Drums, 275 Gallon Totes, 330 Gallon Totes.



**BIOBLEND<sup>™</sup> RENEWABLE RESOURCES LLC**  
 2439 REEVES ROAD - JOLIET, IL 60436  
 PHONE: 630.227.1800  
 www.bioblend.com