

TruGrease AP²

ALL PURPOSE FOOD MACHINERY GREASE

DESCRIPTION:

Foodstream™ TruGrease AP² is a revolutionary, heavy duty lubricating grease and is NSF registered as meeting the guidelines of an H1 product for incidental food contact, for use throughout the plant. **TruGrease AP²** is formulated to protect your equipment against water washout, corrosion, heavy loads, shocks, and other stresses. **TruGrease AP²** bonds with metal surfaces protecting them from water, dirt, and debris. It was designed to handle all the rugged applications found in a food processing plant environment, reducing the need to have more than one grease in the maintenance department as well as reduce downtime.

FEATURES:

- ◆ Heavy duty Extreme Pressure performance.
- ◆ Excellent corrosion resistance.
- ◆ High Dropping Point (>300°C).
- ◆ Enhanced water resistance.
- ◆ Overall operating temperature range is -20°F to 500°F
- ◆ NSF H1 Food Grade and Kosher approved.

TECHNICAL DATA:

	TruGrease	AP ²				
NLGI Grade:	ASTM D217	2				
Color:	Visual	Tan				
Dropping Point, °F (°C):	ASTM D2265	604 (318)				
Penetration, Worked 60	ASTM D217					
Timken OK Load, kg:	ASTM D2509	27.2				
4-Ball EP--	ASTM D2596					
--LWI, kg:		62				
--Weld Point, kg:		500				
4-Ball Wear, mm:	ASTM D2266	.45				
Rust Test Rating:	ASTM D1743	Pass				
Copper Corrosion Rating:	ASTM D4048	1A				
Bomb Oxidation, psi Drop:	ASTM D942	6				
Water Washout, % loss max.:	ASTM D1264	.5				

AVAILABLE PACKAGING:

14oz. Tubes in 10 Pack or 50 Tube Case, 35lb. Pails, 120lb. Kegs, 400lb. Drums



BIOBLEND™ RENEWABLE RESOURCES LLC
 2439 REEVES ROAD - JOLIET, IL 60436
 PHONE: 630.227.1800
 www.bioblend.com